

## Industrial Counting Scale

- Heavy Duty
- Portable and Economical
- Backlit Display



| Model                        | OAC - 1.2   | OAC - 2.4 | OAC - 6                                     | OAC - 12  | OAC - 24 |
|------------------------------|---|-----------|---|---|----------|
| Capacity                     | 2.4 lb  | 6 lb      | 12 lb                                       | 24 lb   | 60 lb    |
| Readability                  | 0.0002 lb   | 0.0005 lb | 0.001 lb                                    | 0.002 lb  | 0.005 lb |
| Displayed Divisions          | 12,000  |           |   |   |          |
| Internal Counting Resolution | 200,000 counts  |           |   |   |          |
| Weighing Units / Functions   | lb / counting   |           |   |   |          |
| Stabilization Time (seconds) | < 1.5   |           |   |   |          |
| Tare Range                   | To capacity by subtraction  |           |   |   |          |
| Power Source                 | Built-in rechargeable battery or external power adapter (included)  |           |   |   |          |
| Construction                 | Stainless steel pan and ABS housing   |           |   |   |          |
| Display                      | 0.6 inches / 15 mm weight display with 0.87 inch / 22 mm high total count display, wide viewing angle backlit LCD |           |   |   |          |
| Pan Size (W x D)             | 9.8 x 8.3 in / 250 x 210 mm all stainless steel   |           | 11.8 x 9.6 in / 300 x 245 mm                | 13.3 x 11.1 in / 337 x 282 mm all stainless steel |          |
| Dimensions (W x D x H)       | 11.22 x 13.23 x 4.65 in / 285 x 336 x 118 mm  |           | 11.8 x 13.23 x 4.65 in / 300 x 336 x 118 mm | 13.3 x 13.23 x 5.3 in / 337 x 336 x 134 mm        |          |
| Operating Environment        | 32° ~ 104° F non condensing R.H. ≤ 85%  |           |   |   |          |
| Net Weight                   | 9.48 lb / 4.3 kg  |           |   |   |          |
| Shipping Weight              | 13.7 lb / 6.2 kg  |           |   |   |          |
| Options                      | RS232C interface or printer interface output  |           |   |   |          |

OAC - 1.2 & 2.4



OAC - 6



OAC - 12 & 24



## Features

Heavy duty construction  
 Low profile, compact size  
 Counting function (see below)  
 Built-in rechargeable battery or external power adapter  
 Accumulation function

Zero tracking  
 Automatic power save  
 Low battery indicator / charge status indicator  
 Auto-calibration function  
 Adjustable feet / spirit level

Wide-angle LCD display with backlight

## Benefits

Will withstand harsh industrial operation  
 Uses less counter space  
 See below  
 Portability - battery lasts a minimum of 200 hours  
 Allows you to add together consecutive weights to arrive at a total  
 Ensures that you always start weighing at zero  
 Conserves battery power  
 Alerts you to change the battery, saving downtime  
 Ensures accuracy  
 Scale remains level for accurate results on uneven working surfaces - Anti-slip  
 Can be seen from a wide viewing range even in poor lighting conditions

### The OAC is equipped with the following state of the art counting features:

Auto piece weight enhancement  
 Accumulation memory for weight and total count  
 Full numerical keypad  
 Over weighing and counting alarm  
 8 x one touch piece weight PLU

Allows for finer counting  
 Gives ability to add together weighings, either by count or weight  
 User friendly operation & fast data entry  
 Ensures fast throughput with fewer mistakes  
 Frequently used component sample weights can be stores in memory for easy retrieval